




00100A8G3P8017

Cable Assembly

6GHz SMA(F)R/A Bulkhead/D flat-SMP(F)R/A for 30cm SS405 Cable Assembly/ 0.Direction

Features

- ✓ High Repeatability
- ✓ Low VSWR




Test Report

Electrical Specifications

Frequency	DC-6GHz
VSWR	1.5:1(Max.)
Impedance	50Ohm
Connection 1	SMA Female Right Angle
Connection 2	SMP Female Right Angle

Material

Part	Material	Plated
1.SMA Connector		
Body	Brass	Gold
Center Pin	Beryllium Copper	Gold
Insulator	Teflon	
2.Cable		
SS405 Coaxial Cable		Blue
3.Adhesive shrink tube		
		Black
4.SMP Connector		
Body	Beryllium copper	Gold
Center Pin	Beryllium Copper	Gold
Insulator	Teflon	
5.Heat Shrink Tube		
		Black




Mechanical

Durability	500 Cycles
------------	------------

Outling Drawing (Unit:mm)

DIMENSIONS	TOLERANCES
0.5~10mm	±0.2
11~100mm	±5.0
101~500mm	±10.0
501~1000mm	±15.0
1001~2000mm	±20.0
2000~5000mm	±50.0





Wake up your further dream.



SS405 Spiral Shielding Coaxial Cable Physical Characteristics

Center Conductor	0.511±0.012mm SPCW
Dielectric Diameter	1.61±0.03mm PTFE
Inner Shield	1.80±0.03mm SPC Tape
Braid	2.10±0.05mm SPC 91% Coverage
Jacket	2.70±0.05mm FEP
Minimum Bend Radius Static	6mm
Minimum Bend Radius Dynamic	25mm

SS405 Spiral Shielding Coaxial Cable Electrical Characteristics

Impedance	50 ± 2ohms		
Capacitance	95 pF/m (nom.)		
Operating Frequency	18GHz		
Operating Temperature	-65~ 180℃		
Shielding Effect	100 dB(Min.)		
Velocity of propagation	69.5%		
Structure	Frequency	Typical Attenuation(dB/m)	Power (Watts CW)
	0.4GHz	0.45	194
	1GHz	0.70	120
	5GHz	1.71	53
	10GHz	2.62	37
	18GHz	3.61	25

整條 Assembly 之 Loss 為以下 3 項數值之加總

1. 接頭 Loss : 0.06 x √ 頻率 (2 端都有接頭則需將此數值 x2)
2. 組裝 Loss : 0.12 (2 端都有組裝則需將此數值 x2)
3. 線材 Loss : 依上述 Maximum Attenuation 換算需求長度之 Loss
4. 晃動測試公差: I/L +/-0.2dB